

## HPT Series Transformers

### PLUG-IN 12VDC AND 24VAC TRANSFORMERS

The HPT Series plug-in 24VAC transformers come in several sizes, the largest with an output rating of 50VA. They have a case-mounting tab to keep them secured to the wall outlet and screw terminals for power lead wires

The HPT Series plug-in 12VDC power supplies come in several sizes, the largest with a regulated output rating of 3000mA. They have a case-mounting tab to keep them secured to the wall outlet and come with a cord with 2.1mm coaxial plug. These are UL/CSA Listed.

The open-frame HPT Series AC transformers come in two sizes and provide lead wires for connections, with a maximum output of 200 VA.

The Honeywell HPT Series of AC and DC transformers are able to be used in a wide range of applications in CCTV, access, and security systems. By supplying low-voltage AC or DC, they are an important part of any security system.

#### Features:

- Built-in thermal protection
- Operating temperature range: -4F to +95F (-20C to +35C), indoor use only
- HPT Series mounts to a standard wall outlet with a screwdown tab
- HPT Series dimensions: approx. 2.5" x 2.2" x 4.0" (6.35m x 55.9m x 101.6m)
- HP2412IL8 is an in-line unit with flying leads
- Open-frame transformers can be used to increase the current of the HPTV power supplies



# HPT Series Transformers

www.honeywellvideo.com

## SPECIFICATIONS:

<b>Technical and Ordering Information</b>	
<b>HPT Series Plug-in Transformers</b>	
<b>HPT2420</b>	24VAC, 20VA Class 2 plug-in with thermal cut-out
<b>HPT2440</b>	24VAC, 40VA Class 2 plug-in with thermal cut-out
<b>HPT2450</b>	24VAC, 50VA Class 2 plug-in with thermal cut-out
<b>HPT Series Open-Frame Transformers</b>	
<b>HPT28100</b>	28 VAC, 100 VA Class 2 open frame with thermal cut-out
<b>HPT28175</b>	28 VAC, 100 VA Class 2 open frame with thermal cut-out
<b>HPT24100</b>	24 VAC, 100 VA Class 2 open frame with thermal cut-out
<b>HPT24200</b>	24 VAC, 200 VA Class 2 open frame with thermal cut-out
<b>DC Converters and Plug-ins</b>	
<b>HPT12DC500</b>	12VDC/500mA plug-in regulated 2.1 mm coaxial plug UL/CSA Listed
<b>HPT12DC1000</b>	12VDC/1000mA plug-in regulated 2.1 mm coaxial plug UL/CSA Listed
<b>HPT12DC1500</b>	12VDC/1500mA plug-in regulated 2.1 mm coaxial plug UL/CSA Listed
<b>HPT12DC3000</b>	12VDC/3000mA plug-in regulated 2.1 mm coaxial plug UL/CSA Listed
<b>HP24121L8</b>	24VAC in, 12VDC/800mA out converter, PTC limited

**NOTE:** Honeywell reserves the right, without notification, to make changes in product design or specifications.