

## HMM12

### 12-INCH MONOCHROME CRT MONITOR

The Honeywell HMM12 is a compact, high quality 12-inch monochrome monitor. The monitor features a sturdy housing and delivers sharp images with over 1000 TV lines of resolution. Unlike conventional monitors, the HMM12 has convenient recessed front panel controls making it easy to setup and adjust, while restricting movement caused by accidental contact.

Installers can easily switch between EIA and CCIR video formats to comply with worldwide video standards. An illuminated green LED beside the power button confirms that power is being supplied to the monitor. The HMM12 features a latching power switch which remains in its set position – either On or Off – eliminating the need to turn the monitor back on in the event of a power loss.

The HMM12 has a composite BNC connector with looping output. The BNC connectors are auto terminating, eliminating the need for installers to set termination switches when using for loop-through video.

#### Market Opportunities

The HMM12 has an optimal viewing distance of five feet or less from the operator's eyes and is ideal for video surveillance and security applications. The HMM12's size and attractive styling are ideal for rack mount or desktop use. The monitor can be easily rack mounted using an optional rack mount kit (HMM12RK1).

#### Features


- >1000 TVL (at center)
- Convenient recessed front panel controls
- Heavy-duty metal cabinet
- EIA or CCIR selectable
- Video loop-through with automatic termination
- Latching power switch
- Rack mountable



## SPECIFICATIONS

| Video                         |  |
|-------------------------------|--|
| Video Standard                | EIA/CCIR   |
| Input Signal Video/PC         | 1Vp-p @ 75 Ohms  |
| Deflection                    | 90° angle  |
| Bandwidth                     | 10 MHz   |
| Resolution                    | >1000 TV lines (at center)   |
| Horizontal Scanning Frequency | EIA: 15.734 kHz<br>CCIR: 15.625 kHz                                      |
| Vertical Scanning Frequency   | EIA: 59.94 Hz<br>CCIR: 50 Hz   |
| Over/Under Scan               | Horizontal: 6.0 ± 2 % over scanning<br>Vertical: 8.0 ± 2 % over scanning |
| Linearity                     | Horizontal: 10% maximum<br>Vertical: 10% maximum                         |
| Front Panel Controls          | •H-Hold •V-Hold •Bright •Contrast<br>• Power LED •Power Switch           |
| Back Panel Controls           | •V-linearity •V-height •EIA/CCIR selector switch                         |
| Electrical                    |  |
| Operating Voltage             | 90 to 264 VAC, 60 Hz/50 Hz   |
| Power Consumption             | 22 W (Maximum)   |
| Power Cable                   | NEMA 5-15P, UL IEC 320 type connector                                    |

| Mechanical             |  |
|------------------------|--|
| Dimensions (W x H x D) | 12.01" x 11.38" x 12.09"<br>(305 mm x 289 mm x 307 mm)                                     |
| Viewable Picture Area  | .39 x .31 sq in<br>254.1 x 201.7 sq mm   |
| Weight                 | 16.09 lbs (7.3 kg)   |
| Construction           | Housing: Steel<br>Finish: Black  |
| Video Inputs           | 1 x BNC (auto-terminating)   |
| Video Outputs          | 1 x BNC (auto-terminating)   |
| Environmental          |  |
| Temperature            | Operating: 32° F to 104° F<br>0° C to 40° C<br>Storage: 14° F to 122° F<br>-10° C to 50° C |
| Relative Humidity      | 10% to 90% (non-condensing)  |
| Regulatory             |  |
| Emissions              | FCC: Part 15, Class B<br>Canada ICES-003   |
| Immunity               | CE: EN 50130-4   |
| Safety                 | UL: UL1950, cUL: CSA C22.2 No. 950<br>DHHS Rules 21  |
| Accessories            |  |
| HMM12RK1               | 12" rack mount kit, black  |



| Ordering |  |
|----------|--|
| HMM12    | 12 inch Monochrome Monitor (black cabinet) |

**NOTE:** Honeywell reserves the right, without notification, to make changes in product design or specifications.

### Honeywell Security

Honeywell Video Systems  
 2700 Blankenbaker Pkwy, Suite 150  
 Louisville, KY 40299  
 1.800.796.CCTV  
 www.honeywell.com

L/HMM12D/D  
 July 2007  
 © 2007 Honeywell International Inc.

